

REMARKS


Applicants respectfully request amendment to the instant application under 37 C.F.R. 1.312 to include correction of a minor error relating to units therein. Specifically, the unit for sheet resistance is changed to " Ω/square " which is well known in the art. To support this knowledge, Applicants provide herewith an excerpt from a textbook "Semiconductor Devices" for the Examiner's consideration.

Entry, therefore, is believed to be fully appropriate under 37 C.F.R. §1.312 since no new matter is added by this amendment.

In the event that the Examiner has any questions relating to this Amendment or to the application in general, it would be appreciated if the Examiner would telephone the undersigned attorney concerning such questions so that prosecution of this application may be expedited.

In view of the above, entry of the same prior to issuance is respectfully requested.

Respectfully submitted,



Jeffrey L. Costellia
Registration No. 35,483

NIXON PEABODY LLP
Suite 900
401 9th Street, N.W.
Washington, D.C. 20004-2128
(202) 585-8000

SEMICONDUCTOR DEVICES

Mauro Zambuto

*Department of Electrical Engineering
New Jersey Institute of Technology*

BEST AVAILABLE COPY

McGraw-Hill Book Company

New York St. Louis San Francisco Auckland Bogota Caracas
Colorado Springs Hamburg Lisbon London Madrid Mexico Milan
Montreal New Delhi Oklahoma City Panama Paris San Juan
Sao Paulo Singapore Sydney Tokyo Toronto

SEMICONDUCTOR DEVICES INTERNATIONAL EDITION

Copyright © 1989

Exclusive rights by McGraw Hill Book Co. — Singapore for manufacture and export. This book cannot be re-exported from the country to which it is consigned by McGraw-Hill.

Copyright © 1989 by McGraw-Hill, Inc. All rights reserved. Except as permitted under the United States Copyright Act of 1976, no part of this publication may be reproduced or distributed in any form or by any means, or stored in a data base or retrieval system, without the prior written permission of the publisher.

1234567890 FSP PMP 89432109

This book was set in Times Roman.
The editors were Alar E. Elken and John M. Morris.
The production supervisor was Denise L. Furey.
Project supervision was done by Santype International Limited.

Library of Congress Cataloging-in-Publication Data

Zambuto, Mauro.
Semiconductor devices/Mauro Zambuto,
p. cm.

Includes bibliographies and index.

ISBN 0-07-072700-7 (text).

ISBN 0-07-072701-5 (solutions manual)

1. Semiconductors. I. Title.

TK 7871.85.Z35

1989

89-16969

621.36 '6-dc19

When ordering this title use ISBN 0-07-180376-2

Printed in Singapore

BEST AVAILABLE COPY

Dr.
Und
qual

picn
field
matr
cons

of th
tan C
New
has c
and t

quan
nuck
indus
most
profe




FIGURE 4.25
Electron mobility in N-type Si vs. temperature for several doping concentrations [9].

temperature, collisions with impurity ions are the prevalent mechanism and the graph rises with $T^{-3/2}$. At high temperature, intrinsic, neutral atom collisions become the determining mechanism and the mobility drops with increasing temperature, following a $T^{-1/2}$ curve. In between there is a transition range of temperatures, where the graph reaches a maximum before beginning to decay. A more comprehensive picture of the phenomenon is given by the empirical graph of Fig. 4.26 [9], in which each curve of constant doping is seen to follow roughly the shape of Fig. 4.25. Notice that, as expected, with increasing dopant concentrations, the position of the maximum is displaced toward higher and higher temperature ranges.

Example 4.2.2 The same specimen as in Example 4.2.1 is brought to a temperature of 500 K. Compute the resistance and comment on the relative contribution of the electrons and holes to conduction.

Solution. From Fig. 4.26, interpolating for $N = 1.9 \times 10^{18} \text{ cm}^{-3}$ and $T = 500 \text{ K}$:

$$\mu_n \approx 220 \text{ cm}^2/\text{V}\cdot\text{s}$$

The intrinsic concentration is computed from (3.3.7):

$$n_i = 3.65 \times 10^{16}$$

This is two orders of magnitude less than N_D , so the approximation of (3.3.13) holds and the minority carrier concentration is

$$p_n = \frac{(3.61 \times 10^{16})^2}{10^{18}} = 1.3 \times 10^{13} \text{ cm}^{-3}$$

as this quantity is still 3 orders of magnitude smaller than the majority carrier concentration, the contribution of the holes to conduction is negligible, and the

conductivity can be computed on the basis of the electrons only:

$$\sigma \approx 1.6 \times 10^{-19} (220 \times 10^{17}) = 0.35 \text{ } \Omega^{-1}/\text{cm}$$

and finally:

$$R = \frac{2}{0.35 \times 10^{-1} \times 2} = 284 \text{ } \Omega$$

Sheet Resistance

In integrated circuits, resistors are often fabricated as thin sheets of cathodic semiconductor material. Supposing the sheet has uniform thickness δ and width w , as shown in Fig. 4.2.7a; then its resistance is

$$R = \frac{L}{\sigma w \delta} \quad (4.2.12)$$

If the resistor is square in shape, as in Fig. 4.2.7b, then $L = w$ and (4.2.12) becomes

$$R_0 = \frac{1}{\sigma \delta} \Omega \quad (4.2.13)$$

Notice that, for a given material and thickness, all square sheets have the same resistance, independently of the size of the square, provided only they have a known as the sheet resistance and is measured in ohms per square (Ω/\square); it depends only on the thickness of the sheet and its average conductivity.

For the integrated circuit of Fig. 4.2.7c, the resistance can then be computed by counting the number of squares in the strip and multiplying by the sheet resistance. Conversely, this method can be used to design the resistor.




FIGURE 4.2.7
Sheet resistance. (a) Sheet resistor of uniform doping, with w , and thickness δ . (b) Square sheet resistor of side L . (c) Typical integrated circuit resistor. A division into squares to ease computation of the total resistance is indicated by the dotted lines.